AUDIO AND VIDEO INSTALLATIONS CENTER

www.s-video-audio.co.il

1080P 2 Mega Pixel IP Camera

IR80M

HD Network IR Waterproof Camera

1/2.5" CMOS Sensor

2.0 Mega Pixel

Support Mult DDNS

1080P Standard Definition

Product Description

◆**TDS-C807RAE2-3** using high-performance dedicated chips designed for multimedia processing, combine with high-performance operating system and standard **H.264 compression** algorithm,with **1080P** standard definition resolution, and collocate a 1/2.5"CMOS sencer chip, so it can restore the true color; for the **dual-stream design**, the picture is more clearer, smoother. it is Builted in web server, easily through a Web browser to acheive the funtion of management to the network camera ,configuration and monitoring.The embedded design can ensure the stability of the system. Using the **double-laser dot lights** with good quality, collocating a constant current source design techniques, it can allows the light board to work for a long time.The network camera applies to the place which needs night surveillance and video such as the bank, supermarket, factory, convenience stores etc.

Advantages of 2 Mega Pixels Series

◆ 1/2.5" CMOS Sencer.

◆ Standard H.264 Compression Algorithm.

◆ 1080P Standard Definition.

◆ Support Mobile Phone Preview(WinCE, Windows Mobile).

◆ Support Multi DDNS(peanutHull,3322,dyndns).

◆ Built In WEB Server,Convenient Remote Control Management.

◆ IR Laser LED Lights Work and Color Turned Black At The Same Time.

◆ Constant Current Source Design,Intrared Lamp Work More Stable.

◆ IP66 Waterproofing Rank.

Specification

Image Sensor	1/2.5" CMOS Sensor
Horizontal Resolution	2 Mega Pixel
Camera System	NTSC/PAL Optional
Min Illumination	0LUX/F1.2 (LED On)
LENS	CS
LENS Interface	6mm，8mm 12mm,16mm,Optional
Quantity of IR LED	2pcs
IR Distance	**Max:80m**
Video Compression Standard	H.264

Image Streaming	32K ～ 4000Kbps
Highest-resolution	**1080P**
Audio Compression Standard	G.711/G.726
Motion Detection	Support
Email Alert	Support
Network Protocol	TCP,UDP,IP,HTTP,DHCP,PPPoE,RTSP,FTP,SMTP,DNS,DDNS,NTP
Ethernet	1 pcs RJ45 10/100Base-T Self-Adaption Ethernet Interface
Waterproofing Rank	IP66
Operating Temp	-20oC~+60oC
Humidity Range	Max: RH80% ; RH90%
Power	DC-12V
Size	200mm*102mm*100mm
N.W	1.19Kg